LED Background Light 150 x 100

Small construction height
With trigger input Pin 4



80 LED's RD 617 nm
80 LED's IR 875 nm
80 LED's BL 469 nm
80 LED's WL 5600 K

Backlight
Transmitted light illumination
Diffuse radiation with diffusing lens
Aluminium housing black
Stainless steel housing (protection class IP69K)
Screw connections for 4 x M4
luminous and very homogeneous

Cable black 300mm permanently connected

Plug connector M12x1 4-pin
+ 24V DC Pin 1
free Pin 2
GND Pin 3
ON/OFF Pin 4



Name	Flat light	Connection	Wavelength	Voltage	Current	Order Number
FLs100x150T RT	LED red, diffuse	4pol. plug 300 mm	617 nm	24 V DC	0.5 A	10115166
FLs100x150T RT IP69K	LED red, diffuse	4pol. plug 300 mm	617 nm	24 V DC	0.5 A	10115208
FLs100x150T IR	LED ir, diffuse	4pol. plug 300 mm	875 nm	24 V DC	0.8 A	10115190
FLs100x150T IR IP69K	LED ir, diffuse	4pol. plug 300 mm	875 nm	24 V DC	0.8 A	10115216
FLs100x150T BL	LED blue, diffuse	4pol. plug 300 mm	469 nm	24 V DC	1.0 A	10115207
FLs100x150T WS	LED white, diffuse	4pol. plug 300 mm	5600 K	24 V DC	1.0 A	10115206

JenCam GmbH
Felsbachstrasse 9
07745 Jena
Germany

Tel +49-(0)3641-2253-0
Fax +49-(0)3641-2253-19
www.jencam.de
info@jencam.de

JENCAM

Pin Assignment



Pin 1	Brown	Power input	+24 V DC/1.4 A
Pin 2	White		
Pin 3	Blue	Central mass	
Pin 4	Black	ON H-level	+5 … 24 V DC/1 mA 0 … + 3 V DC

Trigger

Application without trigger



Trigger



Trigger time variable

$t_{D\,ON}$	Delay time at 5 V DC	750	ns
$t_{D\,OFF}$	Delay time at 5 V DC		
t_F	Flash time	1 - ∞	µs
$t_{T\,min}$	Minimal Trigger time	1	µs
U_T	Trigger Voltage	5…24	V DC

JenCam GmbH
Felsbachstrasse 9
07745 Jena
Germany

Tel +49-(0)3641-2253-0
Fax +49-(0)3641-2253-19
www.jencam.de
info@jencam.de

JENCAM